

DMX CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	PAN	000-255	Movement 0°-540°
2		000-255	Fine movement
3	TILT	000-255	Movement 0°-270°
4		000-255	Fine movement
5	Speed	000-255	Fast to slow
6	RGBW	000-255	Dimmer 0-100%
7	White	000-255	Dimmer 0-100%
8	Strobe	000-255	Slow to fast
10	Colourwheel	000-015	White
		016-023	Colour 1
		024-031	Colour 2
		032-039	Colour 3
		040-047	Colour 4
		048-055	Colour 5
		056-063	Colour 6
		064-071	Combi Colour 1
		072-079	Combi Colour 2
		080-087	Combi Colour 3
		088-095	Combi Colour 4
		096-103	Combi Colour 5
		104-111	Combi Colour 6
		112-119	Combi Colour 7
		120-127	Colour rotation
		128-189	Forward rotation slow to fast
		190-196	Stop
		194-255	Reverse rotation slow to fast
		000-015	Open
		016-031	Gobo 1
10	Gobo	032-047	Gobo 2
		048-063	Gobo 3
		064-079	Gobo 4
		080-095	Gobo 5
		096-111	Gobo 6
		112-127	Gobo 7
		128-189	Forward rotation slow to fast
		190-193	Stop
		194-255	Reverse rotation slow to fast
		000-255	Red 0-100%
11	Colour	000-255	Green 0-100%
12		000-255	Blue 0-100%
13		000-255	White 0-100%
14		000-255	White 0-100%
15	Wash Strobe	000-255	Slow to fast
16	Special	000-119	No function
		200-209	Reset
		210-239	No function
		240-255	Sound action

TECHNICAL SPECIFICATIONS

Rated voltage	: 100-240VAC, 50-60Hz, 1.2-0.6A
LED	: 30Watt White Spot + 48Watt Wash Red, Green, Blue, White
Beam angle	: 13-18°
Illuminance	: 25.000lx @1m
Flash rate	: 1-24 Hz
Colourwheel	: 6 colours + open
Gobo wheel	: 7 gobo's
Fuse	: F3
DMX Channels	: 16
Functions	: DMX, Automatic programs, Sound to light and Master-Slave.
Dimensions per unit	: 160 x 150 x 230mm
Weight (per unit)	: 2.25 kg

Design and product specifications are subject to change without prior notice.

The products referred to in this manual conform to the European Community Directives to which they are subject:

- Low Voltage (LVD) 2014/35/EU
- Electromagnetic Compatibility (EMC) 2014/30/EU
- Restriction of Hazardous Substances (RoHS) 2011/65/EU

